



## Technical Data Sheet

Updated: 8/17/2021

### **HOT SHOT'S SECRET BLUE DIAMOND PAO 10W-30 FULL SYNTHETIC Ultimate Engine Oil**

**Product Overview** Blue Diamond PAO 10W-30 is a 100% pure poly- $\alpha$ -olefin (PAO) Group IV synthetic oil that requires a very small amount of viscosity improvers to meet the weight specifications. The infusion of our patented FR3 Nano-Technology and CK-4 additive package provides unsurpassed levels of longevity and performance while keeping the oil cleaner longer and providing better mileage and horsepower.

Blue Diamond PAO 10W-30 is a fully formulated CK-4 motor oil with high detergency, exceptional oxidation and thermal stability that prevents deposit formation and oil breakdown making longer drain intervals possible. In addition to exceeding the API CK-4 specification, Blue Diamond PAO 10W-30 meets the requirements from Ford for added wear protection as stated in Ford Specification WSS-M2C171-F1. Not all CK-4 specification oils meet both the CK-4 and the Ford specification.

**Applications and Uses** Blue Diamond PAO 10W-30 is recommended for heavy-duty trucks, agriculture, construction and industrial equipment, drilling rigs, stationary engines, turbo charged and racing engines. The CK-4 specification is backwards compatible with CJ-4, CI-4 and CI-4 Plus specification oils.

Blue Diamond PAO 10W-30 is formulated for extreme cold temperature as well as extreme high temperature service.

**OEM Performance**

- Caterpillar ECF-1, ECF-2 and ECF-3
- Detroit Diesel DDC93K218, DDC93K222
- Cummins CES 20081, CES 20086
- Mack EO-O Premium Plus, EOS-4.5
- Deutz DQC III-10 LA
- API CK-4, CJ-4, CI-4, CI-4 Plus
- Ford WSS-M2C171-F1
- Volvo VDS-4, VDS-4.5
- ACEA E7-12, E9-12
- MB 228.31
- MAN 3575
- JASO DH-2
- Renault VI RLD-3, RLD-4

**POWERED BY SCIENCE**



**Benefits**

- Improves cold weather starting compared to conventional oils
- Improves fuel economy up to 3%
- Lowers oil consumption 78% over CJ-4 spec oils
- Reduces wear 71% over CJ-4 spec oils
- Improves power
- Increases film strength
- Improved oxidation stability
- Improved aeration control
- Handles soot 46% better than CJ-4
- Widens operating temperature Range
- Anti-Rust protection
- Reduces DPF plugging
- Reduces shearing
- Reduces friction
- Reduces deposit formation
- Reduces noise and vibration
- Extends oil change interval
- Extends injector, turbo and engine life

Blue Diamond PAO 10W-30 can be ran up to 3 times longer than the manufacturer’s recommended specifications. With the combined use of a Frantz Bypass Oil Filter, scheduled oil analysis program, and Hot Shot’s Secret TBN Booster, your oil can last up to 100,000 miles. Your oil filter should be changed at the manufacturer’s recommended interval even if your oil is in spec.

**Packaging**

Available in:

- 1 quart bottle
- 1 gallon jug
- 5 gallon bucket
- 55 gallon drum

**Typical Properties**

Property	Test Method	Result
Total Base Number, mg/g	D-2896	9.7
Sulfated ash, %	D-874	1.0
Cold Cranking at -25° C, cP	D-5293	2364
Viscosity at 100° C, cSt	D-445	11.1
Minimum flash point, °C (°F)	D-92	245°C ( 473°F)
Stable pour point, °C (°F)	D-97	-45°C ( -47°F)

The Safety Data Sheet is available at <http://www.hotshotsecret.com/print-documents/>.